

CATALOGUE

COPPER FORK INSULATED TYPE TERMINAL (DOUBLE GRIP)





info@swastiklugs.in 🖾 www.swastiklugs.in 🍅





COPPER FORK INSULATED TYPE TERMINAL (DOUBLE GRIP)

SWASTIK Fork Type Light Duty Cable Lugs used for Cable Wire Harness and Low Voltage Application. The terminal barrel is brazed and soft annealed, Which means that the terminal can be crimped either direction. All the terminals are tin plated to avoid oxidation and to achieve maximum corrosion protection. These terminals can be provided with PVC sleeves for protection against electrical shocks and can also be provided with metal reinforced sleeves to maintain a proper grip on conductor insulation.

MATERIAL: ETP GRADE COPPER WITH PVC SLEEVE

STANDARD: BS 1897

RANGE: 1.5 TO 4-6 SQMM

Color coding for insulated terminal

1.5





Size mm2	E	A	С	D	F	В	н	J	C-1	J-1	L-3
1.5	3.5	1.6	3.2	6.8	0.8	5	4.8	13	4.8	10	16.1
1.5	3	1.8	3.4	6.4	0.8	5	3.1	13	4.8	10	15.5
2.5	3.5	2.3	3.9	6.5	0.8	5	4.3	15	5.4	10	16.8
2.5	5	2.6	4.6	10.6	1	6.2	6.2	21	5.4	10	16.2
4-6	4.2	2.3	3.9	8	0.8	5	-	17.5	5.5	10	/-
4-6	3	3.5	5.5	6	1	6	5.5	15	7.1	15	20.5
4-6	3.5	3.5	5.5	6	1	6	5	15	7.1	15	20
			TOLE	RANCE:	: +/- 5%)					0
	1.5 1.5 2.5 2.5 4-6 4-6	1.5 3.5 1.5 3 2.5 3.5 2.5 5 4-6 4.2 4-6 3	mm2 E A 1.5 3.5 1.6 1.5 3 1.8 2.5 3.5 2.3 2.5 5 2.6 4-6 4.2 2.3 4-6 3 3.5	mm2 E A C 1.5 3.5 1.6 3.2 1.5 3 1.8 3.4 2.5 3.5 2.3 3.9 2.5 5 2.6 4.6 4-6 4.2 2.3 3.9 4-6 3 3.5 5.5 4-6 3.5 3.5 5.5	mm2 E A C D 1.5 3.5 1.6 3.2 6.8 1.5 3 1.8 3.4 6.4 2.5 3.5 2.3 3.9 6.5 2.5 5 2.6 4.6 10.6 4-6 4.2 2.3 3.9 8 4-6 3 3.5 5.5 6 4-6 3.5 3.5 5.5 6	mm2 E A C D F 1.5 3.5 1.6 3.2 6.8 0.8 1.5 3 1.8 3.4 6.4 0.8 2.5 3.5 2.3 3.9 6.5 0.8 2.5 5 2.6 4.6 10.6 1 4-6 4.2 2.3 3.9 8 0.8 4-6 3 3.5 5.5 6 1 4-6 3.5 3.5 5.5 6 1	mm2 E A C D F B 1.5 3.5 1.6 3.2 6.8 0.8 5 1.5 3 1.8 3.4 6.4 0.8 5 2.5 3.5 2.3 3.9 6.5 0.8 5 2.5 5 2.6 4.6 10.6 1 6.2 4-6 4.2 2.3 3.9 8 0.8 5 4-6 3 3.5 5.5 6 1 6	mm2 E A C D F B H 1.5 3.5 1.6 3.2 6.8 0.8 5 4.8 1.5 3 1.8 3.4 6.4 0.8 5 3.1 2.5 3.5 2.3 3.9 6.5 0.8 5 4.3 2.5 5 2.6 4.6 10.6 1 6.2 6.2 4-6 4.2 2.3 3.9 8 0.8 5 - 4-6 3 3.5 5.5 6 1 6 5.5 4-6 3.5 3.5 5.5 6 1 6 5	mm2 E A C D F B H J 1.5 3.5 1.6 3.2 6.8 0.8 5 4.8 13 1.5 3 1.8 3.4 6.4 0.8 5 3.1 13 2.5 3.5 2.3 3.9 6.5 0.8 5 4.3 15 2.5 5 2.6 4.6 10.6 1 6.2 6.2 21 4-6 4.2 2.3 3.9 8 0.8 5 - 17.5 4-6 3 3.5 5.5 6 1 6 5.5 15 4-6 3.5 3.5 5.5 6 1 6 5 15	mm2 E A C D F B H J C-1 1.5 3.5 1.6 3.2 6.8 0.8 5 4.8 13 4.8 1.5 3 1.8 3.4 6.4 0.8 5 3.1 13 4.8 2.5 3.5 2.3 3.9 6.5 0.8 5 4.3 15 5.4 2.5 5 2.6 4.6 10.6 1 6.2 6.2 21 5.4 4-6 4.2 2.3 3.9 8 0.8 5 - 17.5 5.5 4-6 3 3.5 5.5 6 1 6 5.5 15 7.1 4-6 3.5 3.5 5.5 6 1 6 5 15 7.1	mm2 E A C D F B H J C-1 J-1 1.5 3.5 1.6 3.2 6.8 0.8 5 4.8 13 4.8 10 1.5 3 1.8 3.4 6.4 0.8 5 3.1 13 4.8 10 2.5 3.5 2.3 3.9 6.5 0.8 5 4.3 15 5.4 10 2.5 5 2.6 4.6 10.6 1 6.2 6.2 21 5.4 10 4-6 4.2 2.3 3.9 8 0.8 5 - 17.5 5.5 10 4-6 3 3.5 5.5 6 1 6 5.5 15 7.1 15 4-6 3.5 3.5 5.5 6 1 6 5 15 7.1 15