

CATALOGUE

COPPER FORK INSULATED TYPE TERMINAL





info@swastiklugs.in 🖎 www.swastiklugs.in








COPPER FORK INSULATED TYPE TERMINAL

SWASTIK Fork Type Light Duty Cable Lugs used for Cable Wire Harness and Low Voltage Application. The terminal barrel is brazed and soft annealed, Which means that the terminal can be crimped either direction. All the terminals are tin plated to avoid oxidation and to achieve maximum corrosion protection. These terminals can be provided with PVC sleeves for protection against electrical shocks.

MATERIAL : ETP GRADE COPPER

WITH PVC SLEEVE STANDARD: BS 1897 RANGE: 1.5 TO 4-6 SQMM



Color coding for insulated terminal



PRODUCT DESCRIPTION: SHEET METAL FORK TYPE LUG STANDARD TYPE, WITH INSULATED SLEEVE

| SWASTIK CAT NO | Size mm2 | E | Α | С | D | F | В | н | J | C-1 | J-1 | L-3 |
|-------------------|-------------|-----|-----|-----|------|-----|-----|-------------|------|-----|-----|---------------|
| RTI-7926 | 1.5 | 3.5 | 1.6 | 3.2 | 6.8 | 0.8 | 5 | 4.8 | 15 | 4.8 | 10 | 20.8 |
| RTI-7927 | 1.5 | 3 | 1.7 | 3.4 | 6.4 | 0.8 | 5 | 3.1 | 13 | 4.8 | 10 | 20.5 |
| RTI-7928 | 2.5 | 3.5 | 2.3 | 3.9 | 6.5 | 0.8 | 5 | 4.3 | 15 | 5.5 | 10 | 21.8 |
| RTI-1025 | 2.5 | 4.2 | 2.3 | 3.9 | 8 | 0.8 | 5 | / - | 17.5 | 5.5 | 10 | /- |
| RTI-7929 | 2.5 | 5 | 2.6 | 4.6 | 10.6 | 1 | 6.2 | 6.2 | 21 | 5.5 | 10 | 20 |
| RTI-7930 | 4-6 | 3.1 | 3.5 | 5.5 | 6 | 1 | 6 | 5.5 | 15 | 7.1 | 14 | 27.5 |
| RTI-7931 | 4-6 | 3.5 | 3.5 | 5.5 | 6 | 1 | 6 | 5 | 15 | 7.1 | 14 | 27 |
| TOLERANCE: +/- 5% | | | | | | | | | | | | |